

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
30 October 2003 (30.10.2003)

PCT

(10) International Publication Number
WO 2003/090448 A3

(51) International Patent Classification⁷: **G09G 1/04**

(21) International Application Number:
PCT/US2003/012176

(22) International Filing Date: 21 April 2003 (21.04.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
60/374,280 19 April 2002 (19.04.2002) US

(71) Applicant (for all designated States except US): **THOMSON LICENSING S.A.** [US/US]; 2 Independence Way, Suite 2, Princeton, NJ 08540 (US).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **GEORGE, John, Barrett** [US/US]; 11408 Lakeshore Drive, Carmel, IN 46033 (US).

(74) Agents: **TRIPOLI, Joseph, S. et al.**; Thomson Licensing Inc., 2 Independence Way, Suite 2, Princeton, NJ 08540 (US).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).


Published:

- with international search report
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

(88) Date of publication of the international search report:
15 April 2004

[Continued on next page]

(54) Title: **FOCUS VOLTAGE AMPLIFIER**



(57) Abstract: A dynamic focus amplifier (17) for generating a dynamic focus voltage for a focus electrode for a cathode ray tube (12) at a capacitive load (C602, C wire, CTI) includes a source of a periodic signal at a horizontal deflection frequency. A pull-down transistor (Q1) is responsive to the periodic signal and coupled to the capacitive load (C602, C wire, CTI) for producing, in accordance with the periodic signal, a first portion of the dynamic focus voltage that decreases, during a first portion of a period of the periodic signal. A storage capacitor (C501) is coupled to the capacitive load (C602, C wire, CTI) for replenishing a charge stored in the storage capacitor (C501) from a charge stored in the capacitive load to develop a control voltage in the storage capacitor (C501). A pull-up transistor is responsive to the control voltage and coupled to a source of a high voltage and to the capacitive load (C602, C wire, CTI) for producing from the high voltage a current that is coupled to the capacitive load. The current develops a second portion of the dynamic focus voltage that increases, during a second portion of the period of the periodic signal, and stores the charge in the capacitive load (C602, C wire, CTI).